



Clamshell Card

Our Clamshell Card is constructed of durable ABS plastic housing. It is a lower cost RFID card solution if compared to the more sophisticated ISO card. Additionally, it is strong, flexible and resistant to cracking and breaking. The card is predominantly used in access control and ticketing application.

Specifications:

Item No.	TC
Dimensions (± 0.2 mm)	85.6(L) mm x 54 (W) mm x 1.9(T) mm (3.370" x 2.125" x 0.075")
Operating Frequency	125 KHz & 13.56 MHz
Reading Range	Depending on the reader design and local installation conditions.
Operating Temperature	-25°C to + 55 °C (-13°F to +131°F)
Storage Temperature	-25°C to + 75 °C (-13°F to +167°F)
Material	Hard Shell: ABS, Cover Foil: PVC
Standard Color	Blank White
Weight	9.0 gm (0.317 oz)
Packaging	2000 pcs (100 pcs/box, 20 boxes/carton)
Available Technologies	EM4100, T5557, Hitag 1/2 Mifare S50, I.CODE SLI etc.
Options	Inkjet marking for ID number Silk screen printing

Ref.: TC-0412

WARRANTY

© RFID SOURCES warrants this product against defects in material and workmanship under normal use and service. The warranty period commences from the date of shipment for a period of one year.

Specifications subject to change without notice.