



## ISO Card

Our ISO Card is a perfect choice for RFID application in both low and high frequencies. The blank white card we offer can be processed with common card printer. Slot punch marks, magnetic stripe and additional customized printing options are available.

Applications include: e-ticketing  
Access Control  
Campus ID  
Customer Loyalty Programs

### Specifications:

| Item No.               | TI                                                                                                                                                                  |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions             | 85.6(L) mm x 54 (W) mm x 0.82(T) mm<br>(3.370" x 2.125" x 0.032")                                                                                                   |
| Operating Frequency    | 125 KHz & 13.56 MHz                                                                                                                                                 |
| Reading Range          | Depending on the reader design and local installation conditions.                                                                                                   |
| Operating Temperature  | -25°C to + 55 °C (-13°F to +131°F)                                                                                                                                  |
| Storage Temperature    | -25°C to + 60 °C (-13°F to +140°F)                                                                                                                                  |
| Material               | PVC<br>(Normal & High Vicat PETG card material available on request)                                                                                                |
| Finish                 | Matte or Gloss                                                                                                                                                      |
| Standard Color         | Blank White                                                                                                                                                         |
| Weight                 | 6.0 gm (0.212 oz)                                                                                                                                                   |
| Packaging              | 2000 pcs (250 pcs/box, 8 boxes/carton)                                                                                                                              |
| Available Technologies | EM4100 (EM4102), T5557, Hitag 1/2/S<br>Mifare S50/S70/Ultralight/DESFire, I.CODE SLI, Legic, etc.                                                                   |
| Options                | Inkjet marking, offset and silk screen printings<br>300 o.e./2750 o.e./3600 o.e./4000 o.e. magnetic stripes<br>Signature panel and laser slot punch marks available |

Ref.: TI-0412

### WARRANTY

© RFID SOURCES warrants this product against defects in material and workmanship under normal use and service. The warranty period commences from the date of shipment for a period of one year.

Specifications subject to change without notice.

tel:+886 4 2534 0159

fax:+886 4 2535 0778

http://www.rfidsources.com

e-mail:info@rfidsources.com