



## TK60 - Proximity Key Tag

TK60 Proximity Key Tag is designed for the application of proximity access control in the field of hotel room entry or membership management. It is available with most popular 125 KHz and 13.56 MHz RFID chip technologies. The key tag can be delivered with blank white or full color customer specific design.

### Specifications:

Item No.	TK60
Dimensions	65.4(L) mm x 25.2(W) mm x 3.7(T) mm (2.574" x 0.992" x 0.145")
Operating Frequency	125 KHz & 13.56 MHz
Reading Range	Depending on the reader design and local installation conditions.
Operating Temperature	-25°C to + 55 °C (-13°F to +131°F)
Storage Temperature	-25°C to + 85 °C (-13°F to +185°F)
Material	PVC+Epoxy
Assembly	Lamination & Epoxy Covered
Protection Class	IP67
Weight	12 g (0.423 oz)
Packaging	1000 pcs (50 pcs/box, 20 boxes/carton)
Available Technologies	EM4100/EM4102, T5557, HT1, HT2, HTS32, HTS256, HTS2048 Mifare 1K, Mifare 4K, Mifare Ultra Light, I.CODE etc.
Options	Custom size available on request. Inkjet marking for ID number available.

Ref.: TK60-0602

### WARRANTY

© RFID SOURCES warrants this product against defects in material and workmanship under normal use and service. The warranty period commences from the date of shipment for a period of one year.

Specifications subject to change without notice.