



TK10 - Key Fob

Our TK10 Key Fob is constructed of durable ABS plastic housing and available with most popular 125 KHz and 13.56 MHz RFID chip technologies. It is designed for the secure personal identification and access control applications where photo IDs are not required.

Customized key fobs are welcome

Specifications:

Item No.	TK10
Dimensions	36.4(L) mm x 30.0 (W) mm x 7.1(T) mm (1.433" x 1.181" x 0.280")
Operating Frequency	125 KHz & 13.56 MHz
Reading Range	Depending on the reader design and local installation conditions.
Operating Temperature	-25°C to + 55 °C (-13°F to +131°F)
Storage Temperature	-25°C to + 75 °C (-13°F to +167°F)
Material	ABS
Assembly	Ultrasonic Welded
Protection Class	IP66
Standard Color	Dark Blue
Weight	4.7 gm (0.166 oz)
Packaging	1200 pcs (60 pcs/box, 20 boxes/carton)
Available Technologies	EM4100, T5557, Hitag 1/2 Mifare S50, I.CODE SLI etc.
Options	Custom color available on request. Inkjet marking for ID number available.

Ref.: TK10-0412

WARRANTY

© RFID SOURCES warrants this product against defects in material and workmanship under normal use and service. The warranty period commences from the date of shipment for a period of one year.

Specifications subject to change without notice.