

Safety Data Sheet

Version 4.4 Revision date 0625/2023

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 **Product identifiers**

Product name :Silicon PowderProduct Number :0141JSCAS-No. :7440-21-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company :	Nanostructured & Amorphous Materials Inc.
	1526 Katy Gap Road, Suite #302
	Houston, TX 77494, USA

Telephone :	+1 281-858-6571
Fax :	+1 281-858-6507

1.4 Emergency telephone number

Emergency Phone #: +1 832-800-0355

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Flammable solids (Category 2), H228 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Warning

Hazard statement(s) H228 Flammable solid.

Precautionary statement(s)

i rooddallonary old	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for
	extinction.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula :	Si
Molecular weight :	28.09 g/mol
CAS-No. :	7440-21-3
EC-No. :	231-130-8

Hazardous components

Component	Classification	Concentration
Silicon		
	Flam. Sol. 2; H228	-

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5.	FIREFIGHTING MEASURES
5.1 E	xtinguishing media
	Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
5.2	Special hazards arising from the substance or mixture Silicon oxides
5.3	Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
5.4	Further information Use water spray to cool unopened containers.
6.	ACCIDENTAL RELEASE MEASURES
6.1	Personal precautions, protective equipment and emergency procedures Avoid Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.
6.2	Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
6.3	Methods and materials for containment and cleaning up Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).
6.4	Reference to other sections For disposal see section 13.
7.	HANDLING AND STORAGE
7.1	Precautions for safe handling
	Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. For precautions see section 2.2.
7.2	Conditions for safe storage, including any incompatibilities
	Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Over time, pressure may increase causing containers to burst Moisture sensitive. Keep in a dry place.
7.3	Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
8. EX	POSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

-				
Component	CAS-No.	Value	Control parameters	Basis
Silicon	7440-21-3	TWA	15 mg/m3	USA. Occupational
				Exposure Limits
				(OSHA) - Table Z-1
				Limits for Air
				Contaminants
		TWA	5 mg/m3	USA. Occupational
				Exposure Limits
				(OSHA) - Table Z-1
				Limits for Air
				Contaminants
		TWA	10 mg/m3	USA. OSHA - TABLE Z-1
				Limits for
				Air Contaminants -
				1910.1000
		TWA	5 mg/m3	USA. OSHA - TABLE Z-1
				Limits for
				Air Contaminants -
				1910.1000
		TWA	5 mg/m3	USA. NIOSH
				Recommended
				Exposure Limits
	Remarks			Ind in silicon dioxide (silica)
		& in various silic	cates.	
		Irritation		
		Gastrointestinal		
		metal fume feve		
		TWA	10 mg/m3	USA. NIOSH
				Recommended
				Exposure Limits
			tree in nature, but is fou	Ind in silicon dioxide (silica)
		&		
		in various silicat	tes.	

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

		nated gloves after use in accordance with applicable laws and ctices. Wash and dry hands.
	Full contact Material: Nitrile rubb Minimum layer thick Break through time: Material tested: Deri	ness: 0.11 mm 480 min
	Splash contact Material: Nitrile rubb Minimum layer thick Break through time: Material tested: Deri	ness: 0.11 mm 480 min
	EN 374, contact the only and must be ev specific situation of a	4 r mixed with other substances, and under conditions which differ from supplier of the CE approved gloves. This recommendation is advisory raluated by an industrial hygienist and safety officer familiar with the anticipated use by our customers. It should not be construed as for any specific use scenario.
	equipment must be	Flame retardant antistatic protective clothing, The type of protective selected according to the concentration and amount of the ce at the specific workplace.
	particle respirator ty engineering controls supplied air respirate	tion ent shows air-purifying respirators are appropriate use a full-face pe N100 (US) or type P3 (EN 143) respirator cartridges as a backup to a. If the respirator is the sole means of protection, use a full-face or. Use respirators and components tested and approved under ment standards such as NIOSH (US) or CEN (EU).
	Control of environ Prevent further leak	mental exposure age or spillage if safe to do so. Do not let product enter drains.
9. Pł	HYSICAL AND CHEMICAL I	PROPERTIES
9.1	Information on basic phy	vsical and chemical properties
	a) Appearance	Form: powder
	b) Odour	Odourless
	b) Odour c) Odour Threshold	Odourless No data available
	c) Odour Threshold	No data available
	c) Odour Threshold d) pH e) Melting point/freezing	No data available No data available

	h) Evaporation rate	No data available
	i) Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 2.
	j) Upper/lower flammability or explosive limits	No data available
	k) Vapour pressure	No data available
	I) Vapour density	No data available
	m) Relative density	2.33 g/mL at 25 °C (77 °F)
	n) Water solubility	insoluble
	o) Partition coefficient: n-octanol/water	No data available
	p) Auto-ignition temperature	No data available
	q) Decomposition temperature	No data available
	r) Viscosity	No data available
	s) Explosive properties	No data available
	t) Oxidizing properties	No data available
9.2	Other safety information No data available	
10. S	TABILITY AND REACTIVIT	Y
10.1	Reactivity No data available	
10.2	Chemical stability Stable under recommende	ed storage conditions.
10.3	Possibility of hazardous re No data available	eactions
10.4	Conditions to avoid Heat, flames and sparks. E	Extremes of temperature and direct sunlight.
10.5	Incompatible materials Strong oxidizing agents, Al	kali carbonates, Calcium, cobalt difluoride, manganese trifluoride
10.6	Hazardous decomposition Other decomposition produ In the event of fire: see see	ucts - No data available
1		

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - rat - 3,160 mg/kg Inhalation: No data available Dermal: No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation

Eyes - rabbit Result: Mild eye irritation - 24 h (Draize Test)

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen OSHA.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information RTECS: VW0400000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been Thoroughly investigated.

12. ECOLOGICAL INFORMATION

- 12.1 Toxicity No data available
- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available
- 12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1346 Class: 4.1 Packing group: III Proper shipping name: Silicon powder, amorphous Marine pollutant: No Poison Inhalation Hazard: No

IMDG

UN number: 1346 Class: 4.1 Packing group: III Proper shipping name: SILICON POWDER, AMORPHOUS Marine pollutant: No

EMS-No: F-A, S-G

ΙΑΤΑ

UN number: 1346 Class: 4.1 Packing group: III Proper shipping name: Silicon powder, amorphous

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed

	ISHEU DY SAINA I	itle III, Section 313.
SARA 311/312 Hazards Fire Hazard		
Massachusetts Right To Know Components		
	CAS-No. 7440-21-3	Revision Date 2007-03-01
Silicon	7440-21-3	2007-03-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Silicon	7440-21-3	2007-03-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Silicon	7440-21-3	2007-03-01
HER INFORMATION Full text of H-Statements referred to under sec	tions 2 and 3.	
Flam. Sol.Flammable solidsH228Flammable solid.		
HMIS Rating		
Health hazard: 1 Chronic Health Hazard: *		
Flammability: 2		
Physical Hazard: 2		
NFPA Rating Health hazard: 0		
Health hazard: 0 Fire Hazard: 0		
Reactivity Hazard: 2		
Further information		
Employers should use this information only as a sup	-	• •
Employers should use this information only as a sup and should make independent judgment of suitability	of this informatio	n to ensure proper use and
Employers should use this information only as a sup	of this informatio	n to ensure proper use and ed without warranty,